

Urban Waste As Resource For Sustainable Environment

Angelo Milone ^{1a}, Daniele Milone ^{1b}, Francesco Claudio Campione ^{2c}, and Salvatore Pitruzzella ^{2d}

¹ DEIM - Dipartimento Di Energia, Ingegneria Dell'informazione, E Modelli Matematici, University of Palermo, Palermo 90128, Italy

² Facoltà di Architettura Università degli Studi Palermo, Viale delle Scienze 14, Palermo 90128, Italy

^a angelo.milone@unipa.it - ^b daniele.milone@unipa.it

^c ecologia2006@libero.it - ^d salvatore.pitruzzella@unipa.it

Keywords: Waste to energy plant, Smart cities, Energy saving

Abstract: The emerging model of waste disposal, develops an integrated approach based on waste reduction, selection, recycling, energy recovery and residual use of landfill. Here we discuss the fundamentals of a proper planning of waste disposal system, specially the thermal recovery, the integration and the methodological approach, either from the environmental and economic point of view.

The growing demand for energy, the resulting environmental problems due to satisfy the demand for energy and the complex-economic system, necessitate the study of new technologies such as energy from municipal solid waste (MSW) obtaining as a result of decrease huge mass of solid waste to sanitary landfill and emissions of landfill gas as (CH_4 and CO_2).

Therefore, we propose to validate a technical, economical and environmental analysis of waste-treatment systems with emphasis on generation of energy.

The recovery of heat from a waste-to-energy plant, can make a useful contribution to the city energy needs. Whilst we have been slow to exploit fully this resource in Sicily, economically in urban areas.

Introduction

The production of waste in recent years has assumed ever increase proportions. This increase can be attributed to the improvement of living conditions and the progress of industrial development, which led to significant increase in consumption and the product life cycle are often shorter. This large production of waste, represent a great loss of resources and pressure on the environment, which is extended on the all environmental components: air, water and soil.

Sustainable waste management implies reducing dependence on landfills and increasing recycling and reuse. Planning urban waste management in this framework, bring up a number of issues like public health and the people's livelihood, considering how changing lifestyles, introduction of new technologies and advances in science have taken advantage of the environment. Sustainable waste management, must therefore adopt techniques that are cost effective and efficient.

Waste as resource for sustainable development

One of the critical issues in smart cities, is waste management that can be defined as the “Collection- Transportation- Processing- Treatment- Recycling or Disposal” of waste materials to reduce their adverse effects on human health or amenities. In sustainable development, economic progress must be in tandem with preserving the environment. Smart cities use technology to optimise the allocation of resources, drive efficiency and support sustainable living.

Wastes need to be seen not as a problem to be disposed, but as a resource for sustainable development. Disposing solid waste is a common problem and efforts are being made to create

Tab. 1. Performance of engines gas and gas turbines

Types cogeneration plants				
	Gas turbine	Alternative engines	Steam turbines	Combined cycle gas-steam
Power Range Standard	1 MW - 250 MW	0,1 MW - 5 MW	0,5MW-200MW	5 MW - 350 MW
Elettrical Performance	30% - 35%	30% - 42%	25% - 35%	40% - 60%
Total return system	75% - 85%	75% - 85%	75% - 85%	75% - 85%
Combustible	Methane or gas fuel	Methane or gas fuel	Any fuel, heat recovery	How to gas turbine + steam turbine
Benefits	Thermal recovery at high temperature	High flexibility, possibility of stopping daily	Allows recovery of waste heat from industrial processes for electricity generation	High electrical efficiency

Recovery energy from MSW

The potential of recovery of energy from MSW through different methods, can be made from knowledge of its calorific value and organic fraction, as under. [5]

The most used technologies for energy recovery are distinguished in thermo-chemical in which both the organic component biodegradable non-biodegradable, contribute to the production of energy in output, and in bio-chemistry where only the biodegradable component of the organic substance, can contribute the production of energy.

The Tables 2 and 3 outlines the performance obtained for the two different technological solutions.

Table 2. Thermo-Chemical conversion

Total waste quantity:	Q	T (Tonnes)	
Net Calorific Value:	NCV	kWh	
Energy recovery potential: (KW/h)		kWh	NCV*Q
Power generation potential:			NCV*Q/24
Conversion efficiency:		kW	0,25
Net power generation potential:		kW	0,25*NCV*Q/24

When NCV= 4,07 kWh the net power generation is $0,042 * Q$

In bio-chemical conversion, only the biodegradable fraction of the organic matter can contribute to the energy output:

Table 3. Bio-Chemical conversion

Total Waste Quantity	Q	T (tonnes)	
Total Organic/Volatile Solids	VS		$0,5*Q$
Say Organic Bio-degradable Fraction			$0,66*VS=0,33*Q$
Typical Digestion Efficiency			60%
Calorific Value of Biogas	CVB	kWh/mc	5,81 kWh/mc
Energy Recovery Potential		kW/h	$V*5,81$
Power generation		kW	$V*5,81/24$
Typical conversion efficiency			0,30

When CVB= 5,81 kW/mc the net power generation is $11,5* Q$

In order to prove the validity of the system technology described, are summarized in table 4 the estimations of the consumption of fossil fuels for heating a 100 m² household

Table 4. Fossil fuel and biofuel cost management

Fossil fuels and biofuels						
Fuel	U.M	Cost (€)	U.M.	Lower Calorific	Performance	Price (€)
Wet Wood	€/kg	0,13	kWh/kg	4,00	85%	0,038
Pellets	€/kg	0,29	kWh/kg	5,00	85%	0,068
Natural Gas	€/mc	0,76	kWh/mc	9,50	85%	0,094
Diesel Fuel	€/l	1,20	kWh/l	10,00	85%	0,141
LPG	€/l	0,90	kWh/l	7,00	85%	0,151

Table 5. Cost for 100 m² household

Fuel	G (days)	H (hours)	Consume (kW)	Cost (€)
Wet Wood	120	10	8	364,8
Pellets	120	10	8	652,8
Natural Gas	120	10	8	902,4
Diesel Fuel	120	10	8	1353,6
LPG	120	10	8	1449,6

The next table 6 shows the example of a smart city of 100.000 inhabitants and the amount of energy obtainable from MSW respectively as power and thermal energy

Table 6. Performance of power and thermal energy recovery for three technical solutions

Production of MSW for 100,000 Inhabitants 150 T/ day	U.M	Steam Turbine	Thermal engine	Gas Turbine
Waste feed- in flow, per hour	kg/h	6250	6250	6250
Waste low heating value	kJ/kg	14651	14651	14651
Thermal energy	kWt	25436	25436	25436
Primary source energy conversion efficiency steam generator / pyro-gasifier	-	0,78	0,60	0,70
Thermodynamic cycle global efficiency	-	0,22	0,37	0,30
Global net efficiency	-	0,19	0,22	0,21
Electric power	kWe	4816	5596	5342

Conclusions

Smart Cities technologies can provide an important contribution to the sustainable development and energy saving. The District Heating ,Cooling and trigeneration system, aims to support communities in their effort to use energy more efficiently.

In Sicily, the consumption of electricity for domestic use (year 2010) was 5.848,3 GWh/year, compared to the total consumption of 18.949,5 GWh, and the consumption of electricity inhabitant/year is 3.783 KWh/ year * inhabitant.

Most of the consumptions are to be attributed to the consumption of power for heat pumps for air conditioning in summer. The total production of solid waste in Sicily in 2009 was 2.408.127 Tonns/year. In this context, the use of the potential of energy from solid waste, can help to reduce Global Warming and Greenhouse Gases Emissions due to increasing demand for fossil fuels for heating, cooling, hot water and electric power in urban areas. [6 - 7]

References and Notes

- [1] Eriksson, O., Finnveden, G., Ekvall, T., Bjorklund, A., 2007. Life cycle assessment for district heating: A compararison of waste incineration, biomass-and natural gas combustion. *Energy Policy* 35, 1346-1362.
- [2] F.C. Campione, A. Milone, D. Milone, 2001. Studio di fattibilità per il teleraffrescamento dai rifiuti solidi, III° Convegno Nazionale “ Utilizzazione termica dei rifiuti “, Abano Terme (PD).
- [3] F.C. Campione, S. Alterio, A. Campodonico, 2007. Biomasse, fanghi di depurazione e CDR: un sistema energetico integrato. *Recycling* n°4.
- [4] Rosen, M.A., Le, M.N., Dincer, I., 2005. Efficiency analysis of a cogeneration and district energy system. *Applied Thermal Engineering* 25, 147-159.
- [5] Soderman, J., 2007. Optimisation of structure and operation of district cooling networks in urban regions. *Applied Thermal Engineering* 27, 2665-2676.
- [6] S. Alterio, F.C. Campione, A. Milone, D. Milone, 2006, A model sustainable development in areas with limited resources, *Proceedings Venice 2006, Biomass and Waste to Energy Symposium Venice, Italy 29 November-1 Dicembre 2006*;
- [7] A. Galatioto, D. Milone, S. Pitruzzella, G. Scaccianoce, Regional policies for sustainability in the Mediterranean countries: the role of a proper HVAC system maintenance in museums, *Applied Mechanics and Materials Vols. 316-317 (2013) pp 1147-1151* © (2013) Trans Tech Publications, Switzerland doi:10.4028/www.scientific.net/AMM.316-317.1147